



Description

Coupler for Metatray insulating trays. Of 60 mm height. This coupler has a click system, which makes it easy to install on the trays. Made of PVC with high corrosion resistance. Allows the joining of different sections of Metatray insulating trays.

Advantages

High anti-corrosion properties.

Material aislante, seguridad eléctrica y reducción de costes en mantenimiento.

Marcado N de Aenor sobre normas de producto EN 61537 y EN 50085. Conformidad CE respecto directiva 2014/35/UE.

Utilizar con kit tornillo aislante DIN603 M8 Metatray. Ref 81000298.

Applications

Solutions



Product data			
Colour	Grey RAL 7035	Impact Strength (J)	6 J
Flange (mm)	60	Working temperature range (°C)	-20 / 60 °C
kg/u	0.112	Fire resistance	GRADO UL94: V0
u	24	UV Behaviour	ULf1 Resistant
Material	PVC		

Protection System
CU - Copper electroplated
PG - Pregalvanised
EZ - Electrogalvanised
BC - Electrogalvanised Bichromate
BK8 - High Resistance Coating
GC - Hot Dip Galvanising
INOX - Stainless Steel
PT - Polyester Paint
AL - Aluminum
LN - Brass or Nickel-plated brass
Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic

Product applications







