









Battens and Weatherproofs

Hospitality, Industrial, Retail

Performance




## Tornado EVO

## Tornado EVO CCT Multi Wattage 600mm Code: ATORE2/1








Category

**Application** 

Specification



Ancillary, Commercial, Education, Healthcare,

## PRODUCT FEATURES

- IP65 non-corrosive batten suitable for industrial applications and ancillary areas
- CCT selectable between 4000K, 5000K and 6500K and power selectable; offering a choice of 2 outputs, in one luminaire
- $\bullet \ \ \mathsf{LED} \ \mathsf{performance} \ \mathsf{allows} \ \mathsf{point}\text{-}\mathsf{to}\text{-}\mathsf{point} \ \mathsf{replacement} \ \mathsf{of} \ \mathsf{existing} \ \mathsf{fluorescent} \ \mathsf{luminaires}$
- Whole luminaire illuminates during emergency operation rather than a small area, allowing less emergency versions required on an installation
- High efficiency up to 160 Lm/W
- Slim sloped diffuser design creates sleek appearance and offers greater light distribution
- Lockable heavy-duty stainless steel clips supplied as standard for added safety and security

GENERAL INFORMATION		
Wattage	9W/18W	
Lumens Delivered	1600lm - 3100lm (4000K)	
Lm/W	160lm/W (4000K)	
Beam Angle	120	
CRI	80	
CCT	4000/5000/6500K	
Input	220/240V	
Operating Temp	-20°C - 40°C	
SDCM	6	
Energy efficiency class	D	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	Grey	
IP Rating	IP65	
Class Protection	1	
Internal / External	Internal / External	
Surface / Recessed / Suspended	Surface, Suspended	
Lumen Depreciation L70 B50	L70 B50 54,000h	
Warranty (Years)	5	
CE Mark	Yes	
Height	80 mm	

www.ansell-lighting.com Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750