




**Product Description:** Utilite<sup>™</sup>CS 20W Colour Switchable IP65 Oval Utility Bulkhead


Utilite<sup>™</sup>CS oval bulkhead has impact resistant polycarbonate housing, providing a tough exterior and making them ideal for all basic industrial, commercial and residential installations. Separate eyelid and grille bezels are available. The range also features colour switchable technology allowing the colour temperature to be set at either 3000K, 4000K or 6500K on site.

| SKU Code   | Wattage | ColorTemp | Lumens | BeamAngle | SKUType      | FinishColor |
|------------|---------|-----------|--------|-----------|--------------|-------------|
| AU-BH220CS | 20      | 3000K     | 2050   | 120       | Non Dimmable | White       |
| AU-BH220CS | 20      | 4000K     | 2300   | 120       | Non Dimmable | White       |
| AU-BH220CS | 20      | 6400K     | 2100   | 120       | Non Dimmable | White       |

**Line Drawing**



**Polar Curve**



**Colour**

## Feature & Benefits

- Colour switchable between 3000K, 4000K and 6500K
- Polycarbonate body and diffuser
- IP65 rated
- IK06 rated
- -20° - +40° ambient operating temperature
- 3 Year Warranty

## Product Specs:

|                          |             |                          |         |
|--------------------------|-------------|--------------------------|---------|
| Input Voltage            | 220~240V AC | Input Frequency          | 50/60HZ |
| Power Factor             | 0.5         | IP Rating                | IP65    |
| Lifetime L70 (hrs)       | 25000hrs    | IK Rating                | IK06    |
| Lamp Base                | None        | Width (mm)               | 146     |
| Length (mm)              | 271         | Weight (Kg)              | 0.321   |
| Projection (mm)          | 76          | Height (mm)              | 76      |
| Product Type             | Bulkheads   | Operating Temp. (Min) °C | -20°C   |
| Operating Temp. (Max) °C | 40°C        |                          |         |

## Compliance & Approvals:



## Warranty:

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.