



PRODUCT-DETAILS

CM-PFS.S

CM-PFS.S Three-phase monitoring relay 2c/o,
L1-L2-L3=200-500VAC 50/60Hz



General Information	
Extended Product Type	CM-PFS.S
Product ID	1SVR730824R9300
EAN	4016779851947
Catalog Description	CM-PFS.S Three-phase monitoring relay 2c/o, L1-L2-L3=200-500VAC 50/60Hz
Long Description	The CM-PFS.S relay is from the CM three-phase monitors range. This relay operates with a rated control supply voltage / three-phase measuring voltage of 200-500 V AC and has a 2 c/o output with contacts rated at 250 V / 4 A. The CM-PFS.S monitors the phase loss and phase sequence. The corresponding threshold values are fixed. The device offers screw connection technology with double-chamber cage connection terminals.
Ordering	
EAN	4016779851947
Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads	
Data Sheet, Technical Information	2CDC112192D0201
Instructions and Manuals	1SVC730730M1000 1SVC730730M0000
CAD Dimensional Drawing	2CDC001079B0201

Dimensions	
Product Net Width	22.5 mm
Product Net Height	85.6 mm
Product Net Depth / Length	103.7 mm
Product Net Weight	0.127 kg

Technical	
Function	Phase failure detection Phase sequence monitoring
Measuring Range	(L-L) 200 ... 500 V AC
Time Range	500 ms start-up delay
Rated Control Supply Voltage (U _s)	(L-L) 200 ... 500 V AC
Rated Frequency (f)	Supply Circuit 50/60 Hz
Output	2 c/o (SPDT) contacts
Terminal Type	Screw Terminals
Rated Operational Current AC-12 (I _e)	(230 V) 4 A
Rated Operational Current AC-15 (I _e)	(230 V) 3 A
Rated Operational Current DC-12 (I _e)	(24 V) 4 A
Rated Operational Current DC-13 (I _e)	(24 V) 2 A
Minimum Switching Capacity	24 V 10 mA
Rated Impulse Withstand Voltage (U _{imp})	Input Circuit 6 kV Output Circuit 4 kV
Rated Insulation Voltage (U _i)	Input Circuit / Output Circuit 600 V Output Circuit 1 / Output Circuit 2 300 V
Degree of Protection	Housing IP50 Terminals IP20
Overvoltage Category	III
Pollution Degree	3
Short-Circuit Protective Devices	Output Circuit NC - F Type Fuses 6 A Output Circuit NO - F Type Fuses 10 A
Electrical Durability	AC-12 100000 cycle
Mechanical Durability	30000000 cycle
Connecting Capacity	Flexible with Ferrule 1x 0.5 ... 2.5 mm ² Flexible with Ferrule 2x 0.5 ... 1.5 mm ² Flexible with Insulated Ferrule 1x 0.5 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.5 ... 1.5 mm ² Flexible 1x 0.5 ... 2.5 mm ² Flexible 2x 0.5 ... 1.5 mm ² Rigid 1x 0.5 ... 4 mm ² Rigid 2x 0.5 ... 2.5 mm ²

Tightening Torque	0.6 ... 0.8 N·m
Wire Stripping Length	8 mm
Recommended Screw Driver	0.8 x 4 4.5 Pozidriv 1
Mounting Position	1 ... 6
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Standards	CAN/CSA C22.2 No.14 IEC/EN 63000 IEC/EN 60255-27 IEC/EN 61000-6-2 IEC/EN 61000-6-3 UL 508

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Output Circuit 300 V AC
Contact Rating UL/CSA	B300
Connecting Capacity UL/CSA	Flexible 1x 18-14 AWG Flexible 2x 18-16 AWG Rigid 1x 20-12 AWG Rigid 2x 20-14 AWG
Tightening Torque UL/CSA	7.08 in·lb
Pilot Duty UL/CSA	B300

Environmental

Ambient Air Temperature	Operation -25 ... +60 °C Storage -40 ... +85 °C
Maximum Operating Altitude Permissible	Without Derating 2000 m

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SVD981001-4501
RoHS Information	1SVD981001-4401
RoHS Status	Following EU Directive 2011/65/EU
Toxic Substances Control Act - TSCA	2CMT2023-006536

Circular Value

End of Life Instructions	1SAC200290H0001
--------------------------	-----------------

Certificates and Declarations

CB Certificate	CB_DK-28908-UL
CCC Certificate	CCC_2005010303165479
CQC Certificate	CQC2005010303165479

cULus Certificate	cULus508_20120829-E140448
Declaration of Conformity - CCC	2020980303000197
Declaration of Conformity - CE	1SVD981014-00
Declaration of Conformity - UKCA	1SVD981014-10
DNV GL Certificate	DNV_GL_TAA000017D

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	97 mm
Package Level 1 Depth / Length	30 mm
Package Level 1 Height	109 mm
Package Level 1 Gross Weight	0.152 kg
Package Level 1 EAN	4016779851947

Classifications

Object Classification Code	B
ETIM 7	EC001441 - Phase monitoring relay
ETIM 8	EC001441 - Phase monitoring relay
ETIM 9	EC001441 - Phase monitoring relay
eClass	V11.0 : 27371803
UNSPSC	39122332
E-Number (Finland)	2712286
E-Number (Sweden)	3860595

Categories

Low Voltage Products and Systems → Control Products → Electronic Relays and Controls → Three Phase Monitors



360°