

# compact smart relay Zelio Logic - 20 I O - 24 V AC - clock - display

Local distributor code: 389838207

SR2B201B

EAN Code: 3389110549713

# Main

Range of product	Zelio Logic
Product or component type	Compact smart relay

# Complementary

Local display	With	
Number or control scheme lines	0240 with ladder programming 0500 with FBD programming	
Cycle time	690 ms	
Backup time	10 years at 25 °C	
Clock drift	12 min/year at 055 °C 6 s/month at 25 °C	
Checks	Program memory on each power up	
[Us] rated supply voltage	24 V AC	
Supply voltage limits	20.428.8 V	
Supply frequency	50/60 Hz	
Maximum supply current	233 mA (without extension)	
Power consumption in VA	6 VA without extension	
Isolation voltage	1780 V	
Protection type	Against inversion of terminals (control instructions not executed)	
Discrete input number	12	
Discrete input voltage	24 V AC	
Discrete input current	4.4 mA	
Discrete input frequency	5763 Hz 4753 Hz	
Voltage state 1 guaranteed	>= 14 V for discrete input	
Voltage state 0 guaranteed	<= 5 V for discrete input	
Current state 1 guaranteed	>= 2 mA (discrete input)	
Current state 0 guaranteed	<= 0.5 mA (discrete input)	
Analogue input number	0	
Input impedance	4.6 kOhm for discrete input	
Number of outputs	8 relay	
Output voltage limits	530 V DC (relay output) 24250 V AC	

Contacts type and composition	NO for relay output	
Output thermal current	8 A for all 8 outputs for relay output	
Electrical durability	AC-12: 500000 cycles at 230 V, 1.5 A for relay output conforming to IEC 60947-5-1 AC-15: 500000 cycles at 230 V, 0.9 A for relay output conforming to IEC 60947-5-1 DC-12: 500000 cycles at 24 V, 1.5 A for relay output conforming to IEC 60947-5-1 DC-13: 500000 cycles at 24 V, 0.6 A for relay output conforming to IEC 60947-5-1	
Switching capacity in mA	>= 10 mA at 12 V (relay output)	
Operating rate in Hz	0.1 Hz (at le) for relay output 10 Hz (no load) for relay output	
Mechanical durability	10000000 cycles for relay output	
[Uimp] rated impulse withstand voltage	4 kV conforming to EN/IEC 60947-1 and EN/IEC 60664-1	
Clock	With	
Response time	50 ms with ladder programming (from state 0 to state 1) for discrete input 50 ms with ladder programming (from state 1 to state 0) for discrete input 50255 ms with FBD programming (from state 0 to state 1) for discrete input 50255 ms with FBD programming (from state 1 to state 0) for discrete input 10 ms (from state 0 to state 1) for relay output 5 ms (from state 1 to state 0) for relay output	
Connections - terminals	Screw terminals, 1 x 0.21 x 2.5 mm² (AWG 25AWG 14) semi-solid Screw terminals, 1 x 0.21 x 2.5 mm² (AWG 25AWG 14) solid Screw terminals, 1 x 0.251 x 2.5 mm² (AWG 24AWG 14) flexible with cable end Screw terminals, 2 x 0.22 x 1.5 mm² (AWG 24AWG 16) solid Screw terminals, 2 x 0.252 x 0.75 mm² (AWG 24AWG 18) flexible with cable end	
Tightening torque	0.5 N.m	
Overvoltage category	III conforming to IEC 60664-1	
Product weight	0.38 kg	

# **Environment**

Immunity to microbreaks	10 ms repeated 20 times	
Product certifications	GL	
	UL	
	CSA	
	C-Tick	
	GOST	
Standards	IEC 61000-4-4 level 3	
	IEC 61000-4-3	
	IEC 60068-2-27 Ea	
	IEC 61000-4-11	
	IEC 61000-4-5	
	IEC 61000-4-12	
	IEC 61000-4-2 level 3	
	IEC 60068-2-6 Fc	
	IEC 61000-4-6 level 3	
IP degree of protection	IP20 (terminal block) conforming to IEC 60529	
	IP40 (front panel) conforming to IEC 60529	
Environmental characteristic	EMC directive conforming to IEC 61000-6-2	
	EMC directive conforming to IEC 61000-6-3	
	EMC directive conforming to IEC 61000-6-4	
	EMC directive conforming to IEC 61131-2 zone B	
	Low voltage directive conforming to IEC 61131-2	
Disturbance radiated/conducted	Class B conforming to EN 55022-11 group 1	
Pollution degree	2 conforming to IEC 61131-2	
Ambient air temperature for	-2040 °C in non-ventilated enclosure conforming to IEC 60068-2-1 and IEC	
operation	60068-2-2	
	-2055 °C conforming to IEC 60068-2-1 and IEC 60068-2-2	
Ambient air temperature for storage	-4070 °C	

Operating altitude	2000 m	
Maximum altitude transport	3048 m	
Relative humidity	95 % without condensation or dripping water	

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.500 cm
Package 1 Width	10.000 cm
Package 1 Length	13.300 cm
Package 1 Weight	365.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	20
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	7.794 kg

# **Logistical informations**

Country of origin

# **Contractual warranty**

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	200
Environmental Disclosure	Product Environmental Profile

# **Use Better**

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	Eee2fc35-1620-4b70-b1d5-206e9240044e
REACh Regulation	REACh Declaration
PVC free	Yes


# **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

# **Dimensions Drawings**


# **Compact and Modular Smart Relays**

# Mounting on 35 mm/1.38 in. DIN Rail




# (1) With SR2USB01 or SR2BTC01

# Screw Fixing (Retractable Lugs)



# (1) With SR2USB01 or SR2BTC01


# **Position of Display**



## Connections and Schema

# **Connection of Smart Relays on AC Supply**


# SR••••1B, SR••••1FU



- (1) 1 A quick-blow fuse or circuit-breaker.
- (2) Fuse or circuit-breaker.
- (3) Inductive load.
- (4) Q9 and QA: 5 A (max. current in terminal C: 10 A).

#### With Discrete I/O Extension Module

SR3B•••B + SR3XT•••B, SR3B•••FU + SR3XT•••FU



(1) 1 A quick-blow fuse or circuit-breaker.


NOTE: QF and QG: 5 A for SR3XT141..

## Performance Curves

# **Compact and Modular Smart Relays**

# **Electrical Durability of Relay Outputs**


(in millions of operating cycles, conforming to IEC/EN 60947-5-1) AC-12 (1)



X: Current (A)

Y: Millions of operating cycles


(1) AC-12: switching resistive loads and opto-coupler isolated solid-state loads, cos ≥ 0.9. AC-14 (1)



X: Current (A)

Y: Millions of operating cycles

(1) AC-14: switching small electromagnetic loads ≤ 72 VA, make: cos = 0.3, break: cos = 0.3. AC-15 (1)



X: Current (A)

Y: Millions of operating cycles

(1) AC-15: switching electromagnetic loads ≥ 72 VA, make: cos = 0.7, break: cos = 0.4.

Image of product / Alternate images

## **Alternative**







