



Product Code: MC25404

Luckinslive 434702259

Description: 4 Pole 2 Module 25A Contactor, 4 x Normally Closed Contacts



General Information

Dimensions (mm)	36 (W) x 81 (H) x 68 (D)
Colour	Light Grey
Rated Operational Voltage (AC) (Ue)	400
Frequency (Hz)	50/60
Rated Operating Current - AC-1 / AC-7a (A)	25
Rated Insulation Voltage (V) (Ui)	500
Endurance Mechanical Operations	>5000000
Endurance Electrical Operations	>100000
Device Terminals	Screwed Lug & Pin
Coil Terminal Capacity - Flexible (mm²)	15 to 2.5
Coil Terminal Capacity - Rigid (mm²)	15 to 2.5
Main Contact Terminal Capacity - Flexible (mm²)	1 to 4
Main Contact Terminal Capacity - Rigid (mm²)	15 to 6
Number Of Poles	4
Ingress Protection	IP20
Operational Temperature (°C)	-5 to +60
Warranty (Years)	3
Coil Terminal Torque - Flexible (Nm)	0.8
Coil Terminal Torque - Rigid (Nm)	0.8
Main Contact Terminal Torque - Flexible (Nm)	0.9
Main Contact Terminal Torque - Rigid (Nm)	0.1

Standards BS EN 60947-4-1, BS EN 61095

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.

Termination Layout

