



ARM916U

**MCB with dangerous arc detection 1M 16A B curve 6kA**

**Technical characteristics**

**Architecture**

Neutral position	right
Number of poles	2 P
Type of pole	1P+N
Fixing mode	DIN rail type O (symmetrical)
Curve	B

**Main electrical features**

Rated operational voltage Ue	230 V
Rated current	16 A
Type of supply voltage	AC

**Voltage**

Rated insulation voltage	400 V
Max operating voltage	253 V
Rated impulse withstand voltage	4 kV

**Electric current**

Rated service breaking capacity Ics AC according IEC 60898-1	6 kA
Rated short circuit breaking capacity Icn under 230V AC according IEC60898-1	6 kA

**Electric current / temperature**

Rating current 30°C	16 A
---------------------	------

**Dimensions**

Depth of installed product	70 mm
Height of installed product	125 mm
Width of installed product	17,5 mm

**Power**

Total power loss under IN	3,82 W
---------------------------	--------

**Endurance**

Electric endurance in number of cycles	2000
Number of mechanical operations	8000

**Capacity**

Number of modules	1
-------------------	---

**Accessories included**

Type of accessory	AFDD
-------------------	------

**Equipment**

Quick connect	no
Can be accessorized	catalog.pageproduct.attribute_boolean.no

**Standards**

	EN 62606 EN 60898-1
Standard text	
European directive WEEE	concerned
<b>Safety</b>	
Protection index IP	IP20
<b>Use conditions</b>	
Operating temperature	-25...70 °C