


OSRA 25 / M25(M)*M20(F)

Ex d reduction adaptor, brass nickel-plated, M25-M20



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



Material	Brass nickel-plated
Temp. range min	-60 °C
Temp. range max	110 °C
Protection class	IP66 / IP67
Type of protection	Ex eb, Ex tb, Ex db
Ex-Certificate	IECEX, ATEX
Thread type outer	M
Ø outer thread	25
Lead outer	1,5
Thread type inner	M
Ø inner thread	20
Lead inner	1,5
Length screw-in thread L	15 mm
Key width SW	31 mm
Collar diameter (E)	34 mm
Total length TL	20 mm
Surface	Nickel-plated
Order no. nickel-plated	50065652
Type	OSRA 25 / M25(M)*M20(F)
Packing unit	1
EAN number	4007685656528
Tariff number	74198090
ETIM-Classification	EC000938

Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

☎ +44-12-08816062 · 📠 +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk

20.02.2025

Your Contact:


WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

 +44-12-08816062 ·  +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk

Other technical data on request / subject to change without notice



Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

☎ +44-12-08816062 · 📠 +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk

Other technical data on request / subject to change without notice