

T8 Pro

08292 T8PRO21-W65

T8 LED Glass 21w 5ft 6500K Frosted

- High performance of up to 142lm/W
- Flicker free
- Save energy by up to 65%



Overview

These Kosnic advanced LED tubes are suitable for all areas, including visually demanding non-transient task areas such as offices and educational premises where users require uniform light to maintain well-being. The LED tubes can directly replace fluorescent tubes in magnetic ballast fittings with no rewiring.



General Information

Ambient Temperature Range (°C)	-20°C to 40°C
IK Rating	IK02
IP Rating	IP20
Nominal Lifetime (h)	50,000 h
Protection Rating	Class I
Installation Area	Internal

Technical Summary

Product Code	T8PRO21-W65
Input Voltage Supply	220-240Vac 50/60Hz
Default Power	21 W
Power Factor	>0.94
Default CCT	6,500 K
SDCM of CCT	<6
CRI	92
Dimmable	N
Flicker	0.20%
Lumens Output Maximum	3,000 lm
Maximum Efficiency	143 lm/W
L80B10 Lifetime (h) @Ta 25 °C	50,000 h
Nominal Lifetime (h)	50,000 h
Weight	0.22Kg
Dimensions (L x W x D) (mm)	1214xØ28

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com




T8 Pro

08292 T8PRO21-W65

Overview

These Kosnic advanced LED tubes are suitable for all areas, including visually demanding non-transient task areas such as offices and educational premises where users require uniform light to maintain well-being. The LED tubes can directly replace fluorescent tubes in magnetic ballast fittings with no rewiring.



IP20



General Information

Ambient Temperature Range (°C)	-20°C to 40°C
IK Rating	IK02
IP Rating	IP20
Nominal Lifetime (h)	50,000 h
Protection Rating	Class I
Installation Area	Internal

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com

