

Polyester Cabinet 400x300x200

Polyester Cabinet



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

Protection class	IP66
Glow wire test	850 °C
Temp. range min	-25 °C
Temp. range max	85 °C
Impact resistance	IK10
Material	Polyester
Product Color	RAL 7035
External dimensions LxWxH	400x300x200mm
Type	Polyester Cabinet 400x300x200
Order no. UK	50108495
Packing unit	1

Additional Info:

- Empty cabinets made of polyester reinforced with fiberglass
- For use in electrical networks
- For surface mounting
- Insulation: Class II
- With lock
- Optional locks: metal key, triangle, padlock
- Door opening: 180°
- Option to put mounting plate in the enclosure (insulating or metallic)
- External fixing to the wall
- Resistant to chemical and atmospheric agents

Specification to the following:

Directive 2014/35/UE

Directive 2011/65/UE (RoHS)

Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

☎ +44-12-08816062 · 📠 +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk

Electrical Low Voltage Regulation
In Accordance with EN 62208 and EN 60670-1

Recommended accessories

Polyester Plate for 400x300x200mm	50108720
Metal Plate for 400x300x200mm	50108725

22.05.2024

Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

 +44-12-08816062 ·  +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk

Other technical data on request / subject to change without notice