

## ONYX WIFI DIRECT

### SLIM DYNAMIC HIGH HEAT RETENTION HEATER WITH WIFI & AI

Displayed model SHOXI222 - Onyx storage heater 2,220 W











#### **DIRECT CONTROL WITHOUT GATEWAYS**

Integrated Wi-Fi module that allows direct connection to the router without the need for intermediate gateways.



#### **HIGH HEAT RETENTION (HHR)**

The quality of its materials means that more than 60% of the stored heat is retained even after 16 hours.



#### **MAXIMUM ENERGY SAVINGS**

The Onyx high heat retention storage heater saves up to 37% more energy than a standard storage heater.<sup>2</sup>



#### **INVERTER OPERATION**

Thanks to the **INVERTER SMART ADAPTIVE TECH** technology, the Onyx storage heater automatically adjusts the fan speed, intelligently and continuously adapting to the heating needs of each room.

This regulation improves the management of energy consumption and ensures constant thermal comfort.



#### **FEATURES**

#### CONTROL AND TECHNOLOGY



Module WiFi Inside



Touch panel with display



Comfort, Eco and Bluetooth Anti-frost mode pairing



Inverter Smart Adaptive Tech



Mg-Fe allov



Single & Dual feed system



Compatible with voice assistants



EFFICIENCY



Automatic charge control



Energy saving



Artificial Intelligence



Open Windows function



Early Start function



TRP consumption meter3



GPS automation





#### FUNCTIONALITY



Programmable product & App



4 pre-installed programmes



Product and App lock



Limited mode for guests



Boost mode max. power



Night saving



Holiday



Countdown

#### DESIGN AND FINISHES





100% metal body



PRODUCT **VIDEO** 



AUGMENTED **REALITY** 




DOWNLOAD APP **ROINTE NEXA** 




**TECHNICAL SPECIFICATIONS** 

MODELS	SHOXI102	SHOXI156	SHOXI222	SHOXI276	SHOXI330	
Rated input +5%/-10% (W)	1020	1560	2220	2760	3300	
Rated output (W)	500	700	1000	1250	1500	
Classification (W)	340	520	740	920	1100	
Max. storage capacity (Wh)	7140	10920	15540	19320	23100	
Empty weight (kg)	22.7	26.1	30.0	35.5	38.5	
Weight with cells (kg)	67	91	115	142	165	
Finish	White RAL 9016					
Required cell packs (units) 4	4	6	8	10	12	
EAN13	8435556163435	8435556163442	8435556163459	8435556163466	8435556163473	

### SCHEME Dimensions in mm.






Model	Height (H)	Width (L)	Depth (D)
SHOXI102	740 mm	580 mm	190 mm
SHOXI156	740 mm	703 mm	190 mm
SH0XI222	740 mm	865 mm	190 mm
SHOXI276	740 mm	1069 mm	190 mm
SHOXI330	740 mm	1069 mm	190 mm

### **BRACKETS INCLUDED**

# Standard WALL **FLOOR**



Model	Width	Height	Depth
Standard	225 mm	123 mm	132 mm
Height	225 mm	203 mm	132 mm

<sup>1)</sup> Compatible with 2.4 GHz Wi-Fi networks. 2) Tests carried out in independent laboratories.

<sup>3)</sup> The figure may vary depending on the circumstances of the electrical installation.
4) Each pack includes 3 power cells.