

TRT038N

7 Day Digital Heating Programmer – 3 Channel

Features & Benefits

- 3 independently programmed channels
- Suitable for fully pumped systems
- Simple push button control (illuminates on setting)
- 3 timed control periods (5 day plus 2 or 7 day)
- Holiday mode, 1 and 2 hour boost function
- Always ON and OFF override mode
- Blue LED screen illuminates upon setting
- Optional automatic summer/winter changeover
- Voltage free change over contacts
- 24 hour factory fitted rechargeable battery backup



Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface
Earth Class Rating	Class II
Operating Temperature	0°C to 40°C
Connection	3 Wire
Setting Type	Digital
Battery Type	3.6V 40mA Rechargeable
Power Reserve	7 Days
Program Modes	24 Hour/7 Day, Holiday Mode, 1 or 2 Hour Boost
Switch Type	Single Pole, Double Throw (SPDT)
Voltage Free Contacts	Normally Open

Data sheet

TRT038N

Climate / Programastat Plus

Mounting Hole Centres (mm)	60
Standby Consumption	<1.5W
Switch Rating	3A Resistive, 1A Inductive
Shortest Switching Time	1 Minute
Programmable Slots	3 ON, 3 OFF (Per Channel)
Cable Entry(s)	Back Entry

General

Weight (g)	281
Height (mm)	100
Width (mm)	150
Depth (mm)	32
Body Construction	Polycarbonate
Product Colour	White
Accessories (Included)	Rawl Plugs, Screws
EAN Number	5012483014448
Guarantee Period	3 Years
Trade Tariff Commodity Code	8536508090

Line Diagrams

