



Product Code: CMA023AG

Description: 20A Double Pole Plate Switch With Neon & Optional Flex Outlet



Representative Image

General Information

Dimensions	86mm (W) x 86mm (H) x 9.5mm (D)
Plate Design & Finish	Rounded Profile Anthracite Grey
Switch	Polar White
Materials	Front Plate & Rocker Switch: Urea Rear Housing: Urea Neon Lens: Polycarbonate Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel
Maximum Voltage	250V~ 50Hz
Load Rating	20A
Plate Fixing Centres	60.3mm
Terminal Size	5mmø
Terminal Torque	1.8Nm
Terminal Capacity	4 x 2.5mm²
Double Pole	Yes
Twin Earth Terminals	Yes
Neon Indicator	Yes (Orange)
Flex Outlet	Yes (10mmø Through Bottom of the Plate)
Ingress Protection	IP20
Back Box Depth	25mm Minimum
Operational Temperature	-5°C to +40°C
Warranty	20 Years
Standards	BS EN 60669-1:1999 +A1:2002 +A2:2008

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

All white & grey urea moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases.

All products have been independently tested and achieved a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.