

Product Code: CMA780AG

Description: 13A 2 Gang Switched Socket with Twin USB Charging Outlet (4.2A)



General Information

Dimensions	146mm (W) x 86mm (H) x 9.5mm (D)
Material Composition	Front Plate: Urea Rear Housing: Nylon Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel Electronics: PCB & Electronic Components
Maximum Voltage	250V~ 50Hz
Fixing Centres	120.6mm
Terminal Size	5mmø
Terminal Torque	2.5Nm
Terminal Capacity	4 x 2.5mm ² , 2 x 4mm ²
Switched	Yes
Single Pole	Yes
Twin Earth Terminals	Yes
USB Charging Output	2 Outputs Each - 5V DC, 2.1A (Total 4.2A)
USB Output Connector	USB Type "A"
USB Standby Current	2mA
Back Box Depth	25mm Minimum
Temperature Rating	-5°C to +40°C
Warranty	20 Years (1 Year for electrical components)
Standards	BS 1363-2: 2016 +A1: 2018 BS EN 62368-1: 2014, BS EN 62680-1-1: 2015

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram supplied with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases.
All products have been independently tested and achieved a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.