Part M Range[™]

Technical Specification

Product Code: CMA035AG Description: 13A 1 Gang DP Switched Socket





Representative Image

General Information

 $\label{eq:definition} \textbf{Dimensions} \qquad 86\text{mm (W)} \times 86\text{mm (H)} \times 9.5\text{mm (D)}$

Plate Design & Finish Rounded Profile Anthracite Grey

Switch Polar White

Materials Front Plate & Rocker Switch: Urea

Rear Housing: Urea Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Maximum Voltage 250V~ 50Hz

Load Rating 13A

Plate Fixing Centres 60.3mm
Terminal Size 5mmø

Terminal Torque 2.5Nm

Terminal Capacity 4 x 2.5mm², 2 x 4mm²

Double Pole Yes
Twin Earth Terminals No
Ingress Protection IP20

Back Box Depth 25mm Minimum

Operational Temperature -5°C to +40°C

Warranty 20 Years

Standards BS 1363-2: 2016 +A1: 2018

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All white & grey urea moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases. All products have been independently tested and achieved a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

